

Non-compact manifolds and computable type

Matea Čelar

University of Zagreb

A set S in a computable metric space is *semicomputable compact* if it is compact and it is possible to effectively enumerate all finite unions of basic open balls which cover S . If it is also possible to effectively enumerate all basic open balls which intersect S , we say that S is *computable compact*. Topology plays an important role in determining the relationship between semicomputability and computability. This is expressed in the notion of *computable type*: topological space A is said to have computable type if any semicomputable compact set in a computable metric space which is homeomorphic to A is necessarily computable compact. More generally, topological pair (A, B) of a space A and its subspace B has computable type if, whenever $f : A \rightarrow X$ is an embedding of A in a computable metric space such that $f(A)$ and $f(B)$ are semicomputable compact, then $f(A)$ is computable compact. In recent years, results regarding computable type have been obtained for certain classes of topological spaces, most notably compact manifolds and simplicial complexes [Ilj13, AH22].

In view of the above definitions, the study of computable type is restricted to compact spaces. However, using a more general notion of semicomputability can yield similar results for non-compact spaces. A set S in a computable metric space is *semicomputable* if its intersection with any closed ball is compact and it is possible to effectively enumerate all finite unions of basic open balls which cover $S \cap \hat{B}_i$, uniformly over rational closed balls \hat{B}_i . In [BI14], it was shown that a semicomputable 1-manifold in a computable metric space must be computable. This approach was later extended to generalized graphs [Ilj20]. In [IS18], it was shown that a semicomputable manifold M (of arbitrary dimension) is computable if there exists a relatively compact open set U in M such that $M \setminus U$ is homeomorphic to $\mathbb{R}^n \setminus B^n$.

In this talk, we survey the techniques used to obtain the aforementioned results and develop them further to study more general non-compact manifolds. In particular, we consider *neighborhoods of infinity* (that is, complements of compact

sets) of non-compact manifolds, and show how topological properties of neighborhoods of infinity influence computable type. For example, we show that the infinite cylinder $S^1 \times \mathbb{R}$ (and $S^n \times \mathbb{R}$ in general) has computable type.

This talk is based on joint work with Zvonko Iljazović.

References

- [AH22] Djamel Eddine Amir and Mathieu Hoyrup. Computability of finite simplicial complexes, 2022.
- [BI14] K. Burnik and Z. Iljazović. Computability of 1-manifolds. *Logical Methods in Computer Science*, 10(2:8):1–28, 2014.
- [IK21] Zvonko Iljazović and Takayuki Kihara. *Computability of Subsets of Metric Spaces*, pages 29–69. Springer International Publishing, Cham, 2021.
- [Ilj13] Z. Iljazović. Compact manifolds with computable boundaries. *Logical Methods in Computer Science*, 9(4:19):1–22, 2013.
- [Ilj20] Z. Iljazović. Computability of graphs. *Mathematical Logic Quarterly*, 66:51–64, 2020.
- [IS18] Z. Iljazović and I. Sušić. Semicomputable manifolds in computable topological spaces. *Journal of Complexity*, 45:83–114, 2018.